

## **Features**

- Bayonet fixing lens.
- Anti-tamper locking screw.
- Stainless steel fixings.


## Approvals

• GOST-R certificate: POCC GB.JB05.H00144.









| _  |       |      |     | -    |
|----|-------|------|-----|------|
| Sr | ) e c | :ifi | cat | in r |

at optimum voltage.

| Light source:           | Filament Lamp E27  |
|-------------------------|--|
| Light output:           | 25W  |
| Function:               | Permanent  |
| L.E.D. colours:         | Amber, Blue, Clear, Green,<br>Red & Yellow                                     |
| Effective Intensity cd: | 32 cd* (peak/effective intensity)  |
| Lens type:              | Prismatic  |
| Mounting:               | Surface mount (Wall mount bracket available)                                   |
| Entries:                | $1 \times 5\text{-}7\text{mm}$ push through grommet $2 \times M20$ cable entry |
| Dimensions:             | ø140 x 177 mm  |
| ngress protection:      | IP65   |
| Housing material:       | High impact UL94 V0 (f1) PC  |
| Terminals:              | 0.5 to 2.5mm <sup>2</sup>  |
| Operating temp:         | -25 to +50°C [-13° to +122°F]  |
| Storage temp:           | -40 to +70°C [-40° to +158°F]  |
| Relative humidity:      | 90% at 20°C [68°F]   |

\*Candela measurements representative of performance with clear lens

## Part Codes

Must be ordered separately

| Version:<br>12-250V | <b>Part code:</b> B450TSB250B/[x]                   |
|---------------------|---|
| [x] = Lens colour:  | A: Amber B: Blue C: Clear G: Green R: Red Y: Yellow |
| Note: Filament lar  | nps not included.                                   |