


ISSUE	MOD No.	INITIAL/DATE
1		INTRODUCTION DH 19-06-2020
2		UKCA Mark added RNP 25-04-2022

GNExCP7-PT-S CALL POINT

Maximum Power: 6.244W
 Input Voltage / Current: 48Vdc max 1A max / 24Vdc 3A max
 Input Voltage / Current: 250Vac 50/60Hz max 3.33A max

MANUAL SIGNALLING BOX FIRE/FEU
 Year / Serial No. FOR WIRING REFER TO INSTRUCTIONS IP66
 201CP7PT5XXXXXX D202-00-201-5_Issue_3 TYPE 4, 4X, 13




WARNINGS
 USE COVER BOLTS CLASS A4-70 : DO NOT OPEN WHEN AN EXPLOSIVE ATMOSPHERE IS PRESENT
 POTENTIAL ELECTROSTATIC CHARGING HAZARD - SEE INSTRUCTIONS : FOR INDOOR OR OUTDOOR USE
 TO REDUCE THE RISK OF IGNITION OF HAZARDOUS ATMOSPHERES, CONDUIT RUNS MUST HAVE A SEALING
 FITTING CONNECTED WITHIN 18 INCHES OF CONDUIT
 CAUTION - RISK OF ELECTRIC SHOCK - MORE THAN ONE DISCONNECT MAY BE REQUIRED TO DE-ENERGIZE THE
 EQUIPMENT BEFORE SERVICING
AVERTISSEMENT:
 UTILISER COUVRIER BOULONS CLASSE A4-70 : NE PAS OUVRIER UN PRESENCE D'ATMOSPHERE EXPLOSIVE
 DANGER POTENTIEL CHARGE ELECTROSTATIQUE - VOIR LES INSTRUCTIONS : POUR USAGE INTERIEUR OU
 EXTERIEUR
 POUR REDUIRE LE RISQUE D'INFLAMMATION DES ATMOSPHERES DANGEREUSES, LES CONDUITES DE CONDUIT
 DOIVENT AVOIR UN RACCORD ETANCHETE RACCORDE A MOINS DE 18 POUCES DE L'ENTREMENT
 ATTENTION - RISQUE DE CHOC ELECTRIQUE - PLUSIEURS SECTIONNEURS PEUVENT ETRE NECESSAIRES POUR
 COUPER L'ALIMENTATION DE L'APPAREILLAGE AVANT D'ENTREPRENDRE L'ENTRETIEN

**GNExCP7-PT-S
 PRODUCT LABEL 1
 UL38**

GNExCP7-PT-D CALL POINT

Maximum Power: 6.244W
 Input Voltage / Current: 48Vdc max 1A max / 24Vdc 3A max
 Input Voltage / Current: 250Vac 50/60Hz max 3.33A max

MANUAL SIGNALLING BOX FIRE/FEU
 Year / Serial No. FOR WIRING REFER TO INSTRUCTIONS IP66
 201CP7PTDXXXXXX D202-00-201-5_Issue_3 TYPE 4, 4X, 13



WARNINGS
 USE COVER BOLTS CLASS A4-70 : DO NOT OPEN WHEN AN EXPLOSIVE ATMOSPHERE IS PRESENT
 POTENTIAL ELECTROSTATIC CHARGING HAZARD - SEE INSTRUCTIONS : FOR INDOOR OR OUTDOOR USE
 TO REDUCE THE RISK OF IGNITION OF HAZARDOUS ATMOSPHERES, CONDUIT RUNS MUST HAVE A SEALING
 FITTING CONNECTED WITHIN 18 INCHES OF CONDUIT
 CAUTION - RISK OF ELECTRIC SHOCK - MORE THAN ONE DISCONNECT MAY BE REQUIRED TO DE-ENERGIZE THE
 EQUIPMENT BEFORE SERVICING
AVERTISSEMENT:
 UTILISER COUVRIER BOULONS CLASSE A4-70 : NE PAS OUVRIER UN PRESENCE D'ATMOSPHERE EXPLOSIVE
 DANGER POTENTIEL CHARGE ELECTROSTATIQUE - VOIR LES INSTRUCTIONS : POUR USAGE INTERIEUR OU
 EXTERIEUR
 POUR REDUIRE LE RISQUE D'INFLAMMATION DES ATMOSPHERES DANGEREUSES, LES CONDUITES DE CONDUIT
 DOIVENT AVOIR UN RACCORD ETANCHETE RACCORDE A MOINS DE 18 POUCES DE L'ENTREMENT
 ATTENTION - RISQUE DE CHOC ELECTRIQUE - PLUSIEURS SECTIONNEURS PEUVENT ETRE NECESSAIRES POUR
 COUPER L'ALIMENTATION DE L'APPAREILLAGE AVANT D'ENTREPRENDRE L'ENTRETIEN

**GNExCP7-PT-D
 PRODUCT LABEL 1
 UL38**

60.0

30.0

NEC/CEC CLASS / DIV:
 Class I Div 2 Group ABCD T5 Ta -55°C to +70°C
 Class I Div 2 Group ABCD T6 Ta -55°C to +60°C
 Class II Div 2 Group FG T4 Ta -55°C to +70°C
 Class III Div 1 & 2 Ta -55°C to +70°C

ATEX/IECEx/UKEx:
 Ex db IIC T5 Gb (Ta -55°C to +70°C)
 Ex db IIC T6 Gb (Ta -55°C to +60°C)
 Ex db IIC T5 Gb X (Ta -55°C to +70°C)
 Ex db IIC T6 Gb X (Ta -55°C to +60°C)
 Ex db IIC T135°C Db (Ta -55°C to +70°C)

II 2G DEMKO 19 ATEX 2101X
 II 2D IECEx ULD 19.0007X
 UK21UKEX213AK

UKCA 0518
 CE 2813

ALL ENTRIES M20x1.5 - IF TEMPERATURE EXCEEDS 60° C AT ENTRY OR 60° C AT BRANCHING POINT
 USE SUITABLY RATED CABLE AND CABLE GLANDS - SEE INSTRUCTIONS

European Safety Systems Ltd. www.e2s.com Impress House, Mansell Road, London W3 7QH UK

**GNExCP7-PT-S
 GNExCP7-PT-D
 PRODUCT LABEL 2
 UL38**

DRAWING TO BS8888:2000
 GEOMETRIC TOLERANCES TO ISO1101:1983
 LINEAR DIMENSIONAL TOLS +/-0.35mm
 ANGULAR DIMENSIONAL TOLS +/-2 deg

STANDARDS
**GNEx CP7
 CALL POINTS**

DRAWN	DATE	19-06-20
D.HOWGILL		
CHECKED	DATE	19-06-20
R.N.POTTS		
APPROVED	DATE	19-06-20
R.N.POTTS		


SURFACE FINISH	WEIGHT (Kg)
MATERIAL	
ALTERNATIVE MATERIAL	

THIS DRAWING AND ANY INFORMATION OR DESCRIPTIVE MATTER
 THEREIN IS COMMUNICATED IN CONFIDENCE AND IS THE
 COPYRIGHT PROPERTY OF EUROPEAN SAFETY SYSTEMS LTD.
 NEITHER THE WHOLE OR ANY EXTRACT MAY BE DISCLOSED,
 LOANED, COPIED OR USED FOR MANUFACTURING OR TENDERING
 PURPOSES WITHOUT THEIR WRITTEN CONSENT.

© EUROPEAN SAFETY SYSTEMS LTD.
 AS PER LATEST DATE OF ISSUE SHOWN ABOVE



EUROPEAN SAFETY SYSTEMS LTD
 IMPRESS HOUSE
 MANSELL ROAD
 ACTON
 LONDON W3 7QH
 WWW.E2S.COM

ALL DIMENSIONS IN MM IF IN DOUBT, ASK - DO NOT SCALE		A3
TITLE GNEx CP7-PT TOOL RESET PUSH BUTTON OPTION F1 FIRE CALL POINT PRODUCT LABEL		
SCALE 1:1	SHEET 1 of 1	DRAWING NUMBER D202-09-201

GNEXP7-PT-S CALL POINT
 Maximum Power: 6.244W
 Input Voltage / Current: 48Vdc max 1A max / 24Vdc 3A max
 Input Voltage / Current: 250Vac 50/60Hz max 3.33A max
 INDUSTRIAL CONTROL EQUIPMENT FOR USE IN HAZARDOUS LOCATIONS
 Year / Serial No. IP66 201CP7PTSDXXXXX TYPE 4, 4X, 13

GNEXP7-PT-S PRODUCT LABEL 1

GNEXP7-PT-D CALL POINT
 Maximum Power: 6.244W
 Input Voltage / Current: 48Vdc max 1A max / 24Vdc 3A max
 Input Voltage / Current: 250Vac 50/60Hz max 3.33A max
 INDUSTRIAL CONTROL EQUIPMENT FOR USE IN HAZARDOUS LOCATIONS
 Year / Serial No. IP66 201CP7PTDDXXXXX TYPE 4, 4X, 13

GNEXP7-PT-D PRODUCT LABEL 1

GNEXP7-PB-S CALL POINT
 Maximum Power: 6.244W
 Input Voltage / Current: 48Vdc max 1A max / 24Vdc 3A max
 Input Voltage / Current: 250Vac 50/60Hz max 3.33A max
 INDUSTRIAL CONTROL EQUIPMENT FOR USE IN HAZARDOUS LOCATIONS
 Year / Serial No. IP66 201CP7PBSDXXXXX TYPE 4, 4X, 13

GNEXP7-PB-S PRODUCT LABEL 1

GNEXP7-PB-D CALL POINT
 Maximum Power: 6.244W
 Input Voltage / Current: 48Vdc max 1A max / 24Vdc 3A max
 Input Voltage / Current: 250Vac 50/60Hz max 3.33A max
 INDUSTRIAL CONTROL EQUIPMENT FOR USE IN HAZARDOUS LOCATIONS
 Year / Serial No. IP66 201CP7PBDDXXXXX TYPE 4, 4X, 13

GNEXP7-PB-D PRODUCT LABEL 1

GNEXP7 -PT-S
 -PT-D
 -PB-S
 -PB-D
 -PM-S
 -PM-D

PRODUCT LABEL 2

GNEXP7-PM-S CALL POINT
 Maximum Power: 6.244W
 Input Voltage / Current: 48Vdc max 1A max / 24Vdc 3A max
 Input Voltage / Current: 250Vac 50/60Hz max 3.33A max
 INDUSTRIAL CONTROL EQUIPMENT FOR USE IN HAZARDOUS LOCATIONS
 Year / Serial No. IP66 201CP7PMSXXXXX TYPE 4, 4X, 13

GNEXP7-PM-S PRODUCT LABEL 1

GNEXP7-PM-D CALL POINT
 Maximum Power: 6.244W
 Input Voltage / Current: 48Vdc max 1A max / 24Vdc 3A max
 Input Voltage / Current: 250Vac 50/60Hz max 3.33A max
 INDUSTRIAL CONTROL EQUIPMENT FOR USE IN HAZARDOUS LOCATIONS
 Year / Serial No. IP66 201CP7PMDXXXXX TYPE 4, 4X, 13

GNEXP7-PM-D PRODUCT LABEL 1

DRAWING TO BS8888:2000 GEOMETRIC TOLERANCES TO ISO1101:1983 LINEAR DIMENSIONAL TOLS +/-0.35mm ANGULAR DIMENSIONAL TOLS +/-2 deg	DRAWN DATE 19-06-20 D.HOWGILL CHECKED DATE 19-06-20 R.N.POTTS APPROVED DATE 19-06-20 R.N.POTTS	SURFACE FINISH WEIGHT (Kg) MATERIAL ALTERNATIVE MATERIAL	THIS DRAWING AND ANY INFORMATION OR DESCRIPTIVE MATTER THEREIN IS COMMUNICATED IN CONFIDENCE AND IS THE COPYRIGHT PROPERTY OF EUROPEAN SAFETY SYSTEMS LTD. NEITHER THE WHOLE OR ANY EXTRACT MAY BE DISCLOSED, LOANED, COPIED OR USED FOR MANUFACTURING OR TENDERING PURPOSES WITHOUT THEIR WRITTEN CONSENT.	EUROPEAN SAFETY SYSTEMS LTD IMPRESS HOUSE MANSELL ROAD ACTON LONDON W3 7QH WWW.E2S.COM	ALL DIMENSIONS IN MM IF IN DOUBT, ASK - DO NOT SCALE 	A3
			EUROPEAN SAFETY SYSTEMS LTD. AS PER LATEST DATE OF ISSUE SHOWN ABOVE	TITLE GNEXP7 PT / PB / PM PUSH BUTTON OPTION A1 CALL POINT PRODUCT LABEL		
				SCALE 1:1 SHEET 1 of 1 DRAWING NUMBER D202-09-211		