	1 2	3	4		5	6	7	8	9		10	
								ISSUE	MOD No.	INITIAL/DATE		-
							1		MA 02-02-2024			
A												A
R												
В												B
	60.0											
	STExCP8-PB-I			STE	ExCP8-PM-I	CALL POINT		STExCP8-PT-I		CALL POINT		
	STExCP8PBSPNAS111RN UI=30V II=500mA PI=1100mW CI=0 LI=0	IP66 / TYPE 4, 4X, 13 Year / Serial No.: 24/1CP8PBI000000		STEx Ui = 30	CP8PMSPNAS1I1RN 0V li=500mA Pi=1100mW Ci=0 Li=0	IP66 / TYPE 4, 4X, 13 Year / Serial No.: 24/1CP8PMI000000		STExCP8PTSPNAS111RN Ui=30V li=500mA Pi=1100mV		IP86 / TYPE 4, 4X, 13 Year / Serial No.: 24/1CP8PTI000000		
С	INDUSTRIAL CONTROL EQUIPMENT FOR USE IN HAZARDOUS LOCATIONS SEE MANUAL D204-05-801-IS			SEE MA	INDUSTRIAL CONTROL EQUIPMENT FOR USE IN HAZARDOUS LOCATIONS SEE MANUAL D2040-06/01-8 ALL ENTIRES MOUTS - JI FTEUPERATURE EXCEEDS 80°C AT ENTRY OR 80°C AT BRANCHING POINT - USE SUITABLE RATED CABLE AND CABLE GLANDS - SEE INSTRUCTIONS				INDUSTRIAL CONTROL EQUIPMENT FOR USE IN HAZARDOUS LOCATIONS SEE MANUAL D204-09.091-5. IF TEMPERATURE EXCEEDS 80° CAT ENTRY OR 80° CAT ALL ENTRIES N201.1 - SE STURE EATED CALE AND CARE LAND CS. SEE INSTRUCTIONS			С
-	WARNING: DO NOT OPEN WHEN AN EXPLOSIVE ATM POTENTIAL ELECTROSTATIC CHARGING HAZARD – SEE INSTRU ENERGISED.	SPHERE IS PRESENT; ICTIONS; DO NOT OPEN WHEN		ENERG	NTIAL ELECTROSTATIC CHARGING HAZARD – SEE INSTRUC GISED.	TIONS; DO NOT OPEN WHEN		POTENTIAL ELECTROSTATIC CHAP ENERGISED.	EN WHEN AN EXPLOSIVE ATMOSPHERE RGING HAZARD – SEE INSTRUCTIONS;	DO NOT OPEN WHEN		
	AVERTISSEMENT: NE PAS OUVRIR UN PRESENCE D'ATMOS POTENTIEL CHARGE ÉLECTROSTATIQUE - VOIR LES INSTRUCT	HERE EXPLOSIVE; DANGER IONS; NE PAS OUVRIR ENERGIE.		POTEN	TISSEMENT: NE PAS OUVRIR UN PRESENCE D'ATMOSPH NTIEL CHARGE ÉLECTROSTATIQUE - VOIR LES INSTRUCTIO	ERE EXPLOSIVE; DANGER NS; NE PAS OUVRIR ENERGIE.		POTENTIEL CHARGE ÉLECTROST	RIR UN PRESENCE D'ATMOSPHERE EX ATIQUE - VOIR LES INSTRUCTIONS; NE	PLOSIVE; DANGER PAS OUVRIR ENERGIE.		
	STExCP8-PE PRODUCT LAB				STExCP8-PM PRODUCT LABE				TExCP8-PT-I DUCT LABEL	1		
									0001 0,000			
_	UL210KEX2133X	Ta -55°C to +70°C)		< <u>(</u> E	II 1G DEMKO 15 ATEX 1589X IECEX ULD 15.0018X ATEX / IECEX / UK Ex is IIC T6 Ga (T UL21UKEX2133X			II 1G DEMKO 15 AT IECEX ULD 15. UL21UKEX213	33X	io +70°C)		
D		up ABCD T6 Ta -55°C to +70°C		ι ι		0 ABCD T6 Ta -55°C to +70°C		Made in the United Kingdom	NEC/CEC CLASS / DIV: Class I Div 1 Group ABCD 2813 NEC CLASS ZONE: Class I Zone 0 AEx ia IIC T			D
									CEC CLASS ZONE: Ex ia IIC T6 Ga Ta -55°C to			
	C2S Excrease Statety Impress House	Mansell Road, London W3 7QH UK			28. Evytemes Ltd. Impress House, M	ansell Road, London W3 7QH UK		European Safety Systems Ltd.	Impress House, Mansell R	oad. London W3 7QH UK		
	STExCP8-PE	www.e2s.com		<u>च</u>	STExCP8-PM	www.e2s.com			TExCP8-PT-I	www.e2s.com		
	PRODUCT LAB	EL 2			PRODUCT LABE	L 2		PRO	DUCT LABEL 2	2		
F												F
-												
F												F
	-			1								
	DRAWING TO BS8888:2000 DRAWN GEOMETRIC TOLERANCES TO ISO1101:1983	DATE	SURFACE FINISH	WEIGHT (Kg)		INFORMATION OR DESCRIPTIVE MATTER	600			$\oplus \subset $	A3	
	LINEAR DIMENSIONAL TOLS +/-0.35mm	M.ABALOS 02-02-2024				OF EUROPEAN SAFETY SYSTEMS LTD.	e 2S warning signals	DO NOT SCALE				-
G	NGULAR DIMENSIONAL TOLS +/-2 deg CHECKED DATE TANDARDS R.N.POTTS 02-02-2024				NEITHER THE WHOLE OR ANY EXTRACT MAY BE DISCLOSED, LOANED, COPIED OR USED FOR MANUFACTURING OR TENDERING PURPOSES WITHOUT THEIR WRITTEN CONSENT.		EUROPEAN SAFETY SYSTEMS LTD IMPRESS HOUSE	LTD TITLE STEXCP8 PT / PB / PM INTRINSICALI SAFE CALL POINT - PRODUCT LABE				G
			ALTERNATIVE MATERIA	۸L		N SAFETY SYSTEMS LTD.	MANSELL ROAD ACTON	SAFE		DRAWING NUMBER		-
	CALL POINTS APPROVED	DATE TS 02-02-2024				DATE OF ISSUE SHOWN ABOVE	LONDON W3 7QH	1:1	1 of 2	D204-09-6	601	
							WWW.E2S.COM					-
	I											

1	2 3	4	5 6	7 8	9 1	0
			I		SSUE MOD No. INITIAL/DATE	
					1 Introduction MA 02-02-2024	
A						A
_						
3						В
	60.0					
_						
STExCP8-PB STExCP8PBSPNA	S1IRRN IP66 / TYPE 4, 4X, 13	STExC	CP8-PM-IR CALL POINT P8PMSPNAS1IRRN IP60 / TYPE 4, 4X, 13	ST	TExCP8-PT-IR CALL POINT TExCP8PTSPNAS1IRRN IF06 / TYPE 4, 4X, 13	
INDUSTRIAL CONTRO	PI = 1100mW Ci = 0 Li = 0 Year / Serial No.: 24/1CP88PBIR000000 _E0JulPMENT FOR USE IN HAZARDOUS LOCATIONS		II = 500mA PI = 1100mW CI = 0 LI = 0 Year / Serial No. 24/1CP8PMIR000000 KIAL CONTROL EQUIPMENT FOR USE IN HAZARDOUS LOCATIONS IUAL D204-00-061-IS	INC	=30V li=500mA Pi=1100mW Ci=0 Li=0 Year/Seria No: 24/1CP8PTIR000000 2USTRIAL CONTROL EQUIPMENT FOR USE IN HAZARDOUS LOCATIONS	
	80143 IF TEMPERATURE EXCEEDS 60°C AT ENTRY OR 60°C AT SES SUITABLE RATED CABLE AND CABLE GLANDS - SEE INSTRUCTIONS DO NOT OPEN WHEN AN EXPLOSIVE ATMOSPHERE IS PRESENT; TATIC CHARGING HAZARD - SEE INSTRUCTIONS DO NOT OPEN WHEN	ALLENT BRANCH WARNIN	RIES M20/1 5 - IF TEMPERATURE EXCEEDS 00°C AT ENTRY OR 00°C AT ING POINT - USE SUITABLE RATED CABLE AND CABLE GLANDS - SEE INSTRUCTIONS 05 DO NOT OPEN WHEN AN EXPLOSIVE ATMOSPHERE IS PRESENT:	ALL BR	E MANUAL 2024-00-601-IS LENTRIES M20x1.5 - IF TEMPERATURE EXCEEDS 80°C AT ENTRY OR 80°C AT ANCHING POINT - USE SUITABLE RATED CABLE AND CABLE GLANDS - SEE INSTRUCTIONS ARNING: DO NOT OPEN WHEN AN EXPLOSIVE ATMOSPHERE IS PRESENT;	C
ENERGISED. AVERTISSEMENT:	NE PAS OUVRIR UN PRESENCE D'ATMOSPHERE EXPLOSIVE; DANGER	ENERGI	SSEMENT: NE PAS OUVRIR UN PRESENCE D'ATMOSPHERE EXPLOSIVE; DANGER		TRITIAL ELECTROSTATIC CHARGING RAZARD - SEE INSTRUCTIONS; DO NOT OPEN WHEN ERGISED. ERTISSEMENT: NE PAS OUVRIR UN PRESENCE D'ATMOSPHERE EXPLOSIVE; DANGER TENTIEL CHARGE ÉLECTROSTATIQUE - VOIR LES INSTRUCTIONS, NE PAS OUVRIR ENERGIE.	
POTENTIEL CHARGE I	LECTROSTATIQUE - VOIR LES INSTRUCTIONS; NE PAS OUVRIR ENERGIE.		IEL CHARGE ÉLECTROSTATIQUE - VOIR LES INSTRUCTIONS, NE PAS OUVRIR ENERGIE			
_	STExCP8-PB-IR PRODUCT LABEL 1		STExCP8-PM-IR PRODUCT LABEL 1		STExCP8-PT-IR PRODUCT LABEL 1	
				_		
	EMK0 15 ATEX 1589X ATEX / IECEx / UKEx: CEx ULD 15 0018X Ex ia IIC T4 Ga (Ta -55°C to +70°C) L21UKEX2133X , NEC/CEC CLASS / DIV:	(Ex	DEIMON 15 ATEX 1580X ATEX/10Ebr / UKBC II 1G IEEx LUD 15 0018X Ex ini IC 14 Ga (Ta -55°C to +70°C) UL21UKEX2133X MECICEP C1 46 Ba (Ta -55°C to +70°C)	<	EXX II 16 DEMMO 15 ATEX 1580X ULC TUKEX 2133X ATEX / IECEX / UME:: EXX IECE / UME:: Exial IC T4 Ga (Ta-SFC to +70°C) ULC TUKEX 2133X Exial IC T4 Ga (Ta-SFC to +70°C)	
	dom Class I Dir 1 Group ABCC 14 Ta -55°C to +70°C 2813 NEC CLASS ZONE: Class I Zone 0 AExia IIC T4 Ga Ta -55°C to +70°C	L	NEC/CDS C (JASS / DV/ Class I DV/ 1 Group APCD T4 Ta -55°C to +70°C VS 0518 0518 C 2813 NEC C LASS ZONE: Class I Zone A Exial IIC T4 Ga Ta -55°C to +70°C		de in the United Kingdom NEO/CEC CLASS / OW Class I Div 1 Group ABCD T4 Ta -55°C to +70°C Class I Div 1 Group ABCD T4 Ta -55°C to +70°C Class I Zone 0 AExia III CT 4 Ga Ta -55°C to +70°C	ן טן
	CEC CLASS ZONE E la lii C 14 Ga Ta - 55° C to +70° C					
	afety Impress House, Mansell Road, London W3 70H UK			-	Ex is IIC 74 Garta - 55°C to +7°C	
Carl Systems Lt	STExCP8-PB-IR	(# <u>2</u>	Sistems Ld. Impress House, Mansell Road, London W3 70H UK Systems Ld. STExCP8-PM-IR		European Safety Impress House, Mansell Road, London W3 70H UK Systems Ltd. WWWe2s.com STExCP8-PT-IR	
	PRODUCT LABEL 2		PRODUCT LABEL 2		PRODUCT LABEL 2	
_						
						E
_						
_						
F						
		SURFACE FINISH WEIGHT (Kg)				
DRAWING TO BS8888:2000 GEOMETRIC TOLERANCES TO ISO1101:1983	DRAWN DATE M.ABALOS 02-02-2024		THIS DRAWING AND ANY INFORMATION OR DESCRIPTIVE MATTER THEREIN IS COMMUNICATED IN CONFIDENCE AND IS THE		ALL DIMENSIONS IN MM	43
LINEAR DIMENSIONAL TOLS +/-0.35mm ANGULAR DIMENSIONAL TOLS +/-2 deg	M.ABALOS 02-02-2024	MATERIAL	COPYRIGHT PROPERTY OF EUROPEAN SAFETY SYSTEMS LTD. NEITHER THE WHOLE OR ANY EXTRACT MAY BE DISCLOSED,		DO NOT SCALE	
G	CHECKED DATE R.N.POTTS 02-02-2024		LOANED, COPIED OR USED FOR MANUFACTURING OR TENDERING PURPOSES WITHOUT THEIR WRITTEN CONSENT.	EUROPEAN SAFETY SYSTEMS LTD IMPRESS HOUSE	SAFE CALL POINT - PRODUCT LA	1171
STANDARDS STExCP8		ALTERNATIVE MATERIAL		MANSELL ROAD	SCALE SHEET DRAWING NUMBER	
CALL POINTS	APPROVED DATE R.N.POTTS 02-02-2024		C EUROPEAN SAFETY SYSTEMS LTD. AS PER LATEST DATE OF ISSUE SHOWN ABOVE	LONDON W3 7QH	1:1 2 of 2 D204-09-60)1
				WWW.E2S.COM		-